

SERVICE BOXES & vaults

LIGHT WEIGHT - SAVES TIME = SAVES MONEY!!


1/3 to 1/10 the weight of standard concrete boxes - easily installed by 1 or 2 men without heavy equipment.

HIGHEST STRENGTH

Special combinations of polymer concrete and fiber reinforced polyester – 3 to 4 times the compressive strength of concrete and has the tensile strength of steel.

LONGEST LIFE

Projected 30 or more years – based on past installations in all climates.



TWO MEN EASILY HANDLE A SERVICE BOX.



ADJUST TO GRADE OPTION.

ADDITIONAL FEATURES:

- Boxes can be made in **any depth** from 12 to 48 inches. Extensions from 6 to 24 inches are available.
- Available with or without **integral bottoms** on boxes 30 x 48 and larger.
- **Adjust to grade option** available on boxes 30 x 48 and larger. Vertical adjustments including tilting to 4 inches can be made in minutes. No grouting necessary and adjustments can be made during installation or at any time afterwards.
- **Knockouts** are easily made in the field with a wood hole cutting saw or ordered with knockouts already cut. **Conduit terminators** are also available.
- **Racks** can be cast into the box as optional equipment on boxes 30 x 48 and larger. **Pulling-eyes** can also be provided on these larger boxes.
- **Tongue and groove** interlocking design in large two or three piece covers speed installation and removal.
- 24 x 36 or smaller covers are one piece, 30 x 48, 30 x 60 and 36 x 60 – one or two pieces, 48 x 78 – two pieces and 48 x 96 – three or four pieces.
- Bolting covers to boxes is simplified by utilizing **captive stainless steel bolts** and “**self centering**” fasteners that are replaceable.